

www.medmarine.com.tr
info@medmarine.com.tr
ISTANBUL/TURKEY



70 kN at 0-27 m/min

200 kN electric frequency controlled towing

Brake holding force in 1st layer : 1000

Type: DTH 45-90P, SWL: 45 tons

Electric capstan SWL 30kN

DATA quick release disc type towing hook

1 x 180 kg (HHP) short link chain 19mm Gr3

Rubber, cylinder and W type bow fender, D type

Electric anchor capstan, max. 3000 kg

Force and speed ranges : 200 kN at 0-10 m/min

winch one towing drum



GENERAL

DESIGN Robert Allan Ltd. RAscal 2100-Z BASIC FUNCTIONS Towing, pushing, mooring, fire-fighting CLASSIFICATION RINA C &HULL, &MACH, TUG UNRESTRICTED NAVIGATION, & AUT-UMS INWATERSURVEY FIREFIGHTING SHIP E

DIMENSIONS

| LENGTH O.A. | 21.40 m |
|--------------------------|---------|
| BEAM | 11.30 m |
| DEPTH | 5.10 m |
| DRAFT _{EXTREME} | 4.00 m |
| GROSS TONNAGE | < 300 |
| | |

TANK CAPACITIES

| FUEL OIL | 47,20 m ³ |
|-------------|----------------------|
| FRESH WATER | 10,80 m ³ |

PERFORMANCES

| BOLLARD PULL | 35 tons |
|--------------|--------------------|
| SPEED | 12 knots (approx.) |

PROPULSION SYSTEM

| MAIN ENGINES | CATERPILLAR C32 |
|------------------------|-----------------------|
| TOTAL POWER | 2 x 1080kW @ 2000 rpm |
| EMISSION STANDARD | IMO Tier II |
| AZIMUTHING STERN DRIVE | STEERPROP SP 175T |
| PROPELLERS | 1800 mm diameters |
| SHAFTING | Carbon Shaft |
| | |

ACCOMMODATION

Accommodation for 5 people (Opt. 8 people but max. 5 people for MLC compliance), high-quality and great comfort.

DECK EQUIPMENT

FORE TOWING WINCH

TOWING HOOK

CAPSTAN ANCHORS & CHAIN ANCHOR CAPSTAN FENDERS

AUXILIARY EQUIPMENT

| GENERATOR SET | 2 x JOHN DEERE 6068TFM50, 80 ekW |
|--------------------------|---|
| FRESH WATER SYSTEM | Hydrophore and UV filter combined heater |
| MACHINERY COOLING SYSTEM | Plate cooler type |
| AIR-CONDITIONING | HEINEN HOPMAN: |
| | Secondary AC unit in wheelhouse |
| | Cold climate package |
| | Hot climate package |
| FIFI E SYSTEM | $1 \times M/E$ driven fi-fi pump Capacity; 600 m ³ /hour |
| | 1 x Monitor : Foam/water monitor with remote |
| | operated, electric controls |

around the hull

NAUTICAL AND COMMUNICATION EQUIPMENT

SEARCHLIGHT RADAR SYSTEM MAGNETIC COMPASS AUTOPILOT GPS ECHOSOUNDER VHF VHF hand-held SSB NAVTEX AIS EPIRB SART 2 x 230 V - 2000 W (Remote Controlled) Furuno FAR 2117 Cassens & Plath Kotter Simrad AP-50 Furuno GP-150 Furuno LS-6100 2x Sailor Compact 6222 (one with DSC) 2x Jotron TR-20, GMDSS approved Furuno FS-1575 Furuno NX-700 Furuno FA-150 Jotron Tron-40S Jotron Tron Sart

OPTIONAL

RESCUE BOAT CRANE RESCUE BOAT Manual Operated Crane SWL: 0.5 tonnes REDSEA RS-A-380 foldable rescue boat

