

MED-A2885

Restar 2800



GENERAL

DESIGN	Robert Allan Ltd. RAStar2800
BASIC FUNCTIONS	Towing, pushing, escorting, mooring, fire-fighting
CLASSIFICATION	RINA; C ✕ HULL ✕ MACH
	Escort tug – fire-fighting ship 1 – water-spraying oil recovery ship – flash point > 60°C Unrestricted navigation
	AUT UMS – AUT PORT – SYS NEQ – COMF NOISE C – COMF VIB C GREEN STAR 3 – INWATERSURVEY

DIMENSIONS

LENGTH O.A.	28,40 m
BEAM	13.00 m
DEPTH	5,40 m
DRAFT BASELINE	4,10 m
DRAFT EXTREME	5,70 m
GROSS TONNAGE	< 500

TANK CAPACITIES

FUEL OIL	151,00 m ³
POTABLE WATER	20,40 m ³
FRESH WATER	53.80 m ³
SEWAGE WATER	5,90 m ³
GREY WATER	5,90 m ³
OILY WATER	4,00 m ³
LUBRICATION OIL	2,50 m ³
FOAM	8,00 m ³

PERFORMANCES

BOLLARD PULL	80 tons
SPEED	12.5 knots (approx.)

PROPULSION SYSTEM

MAIN ENGINES	CATERPILLAR 3516C 2x2525 kW @ 1800 rpm
EMISSION STANDARD	IMO Tier II (Tier III Optional)
AZIMUTHING STERN DRIVE	KONGSBERG US 2555 FP with slipping clutch for FIFI 1
PROPELLERS	2800 mm diameters
SHAFTING	Carbon Fiber Shaft

ACCOMMODATION

Accommodation for 10 people MLC-compliant high-quality and great comfort accommodation is climate-controlled and includes a master cabin, an officer cabin, and four double crew cabins.

DECK EQUIPMENT

FORE TOWING WINCH
with two drums

KONGSBERG Heavy duty escort towing winch
Brake Holding Load @ 1st Layer: 250 tonnes
Recovery
Nom. pull / low speed /1st layer : 72t / 11 m/min
Nom pull / high speed /1st layer : 14t / 49 m/min
Rendering
Nom. pull / low speed /1st layer : 101t / -48 m/min
Nom pull / high speed /1st layer : 23t / -91m/min

AFT TOWING WINCH
warping head

KONGSBERG Hydraulic towing winch with
Brake Holding Load @ 1st Layer: 200 tonnes
Recovery
Nom. pull / low speed /1st layer :56t / 13 m/min
Nom pull / high speed /1st layer : 10t / 57 m/min

AFT TOWING HOOK

DATA quick release disc type towing hook
Type DTH 90-135 P

TOWING PINS

DATA DTP 12SH

ANCHORS & CHAIN

2 x 495 kg (HHP) Short link chain 22 mm Gr 2

FENDERS

Rubber, Cylinder, W and D type fendering

AUXILIARY EQUIPMENT

GENERATOR SET	2 x C4.4 99 ekW 1500 rpm 50hz
FRESH WATER SYSTEM	Hydrophore and UV filter combined heater
MACHINERY COOLING SYSTEM	Box cooler type
AIR-CONDITIONING	HEINEN HOPMAN: Secondary AC unit in wheelhouse Cold and Hot climate package
FIFI 1 SYSTEM	2x M/E driven fi-fi pump Capacity; 1375 m ³ /hr. 2 x Monitor : Foam/water monitor with remote operated, electric controls

NAUTICAL AND COMMUNICATION EQUIPMENT

GMDSS A3 AREA	
SEARCHLIGHT	2 x 230 V, 2000 W (Remote Controlled)
RADAR	FURUNO FAR-1518-BB
GPS NAVIGATOR	FURUNO GP-170
AIS CLAS A	FURUNO FA-170
SATELLITE COMPASS	FURUNO SC-70
MAGNETIC COMPASS	REFLECTA A/3
NAVTEX	FURUNO NX-700B
EPIRB	JOTRON TRON 60S
SART	JOTRON TRON SART 20
AUTOPILOT	RAYTHEON ANSCHUTZ NP 60
BNWAS	FURUNO BR-500
INTERCOM	PHONTECH CIS-3100
VHF	JOTRON TRON TR30
INMARSAT-C	FELCOM-19/SSAS
SPEED LOG	FURUNO DS-80
ECHO SOUNDER	FURUNO: FE-800

OPTIONAL EQUIPMENT

DECK CRANE
RESCUE BOAT CRANE & RESCUE BOAT